



Acrylic Gloss Product Advice Sheet

Description

A tough, quick drying multi-surface acrylic gloss paint for use in many interior or exterior applications. Dries to a smooth subtle gloss finish with excellent covering power and adhesion. Recommended for use in kitchens and bathrooms. Compared to traditional gloss paints it has a much lower odour during application and drying.

Surfaces

Suitably primed woodwork, primed iron and steel surfaces, MDF, aluminium, copper and PVC. Ideal for kitchens and bathrooms and for use on radiators.

Pack Sizes

1 litre

Colour Range

Little Greene and others on request

Spreading Rate

Up to 14 square metres per litre depending on surface profile and porosity.

Drying Rate

Normally touch dry in 1-2 hours. Recoatable in 4 hours.

Environment

Manufactured to BS EN ISO 14001:2004 standards

VOC content Low (less than 2%)

Complies with European Commission VOC Directive 2004/42/CE

Technical Information

Sheen Level

75-85%

Spraying

(Conventional) Dilute 5% with clean water
(Airless) Use 13 – 15 thou tip

Specific Gravity

1.02-1.27 depending on colour

Solids by Volume

36% approximately

Dry film Thickness

25-30 microns per coat on smooth surfaces



Acrylic Gloss Product Advice Sheet

Preparation

Surfaces must be clean, dry and free from loose and flaking material, dirt, grease etc. Repairs should be carried out prior to painting. Areas contaminated with fungal or algal growth should be treated with a proprietary fungicidal wash or with 25% household bleach before painting. Surfaces previously treated with oil-based paint should be lightly abraded before painting.

Application

Stir well before use. Ready for use by brush, roller or airless spray. On porous surfaces up to 5% water may be added to assist application. On very porous surfaces e.g. plaster up to 25% water may be necessary. Two coats over a suitably primed surface are recommended for maximum protection.

Clean up

Equipment should be cleaned with water immediately after use.

Precautions

Always read the can label before use. Do not apply to surfaces below 5°C or if there is a risk of heavy rain or frost during application or drying.

Disclaimer

All the information submitted on this sheet is correct to the best of our knowledge and experience. The Little Greene Paint Company reserves the right to modify data and systems sheets and procedures with reference to usage and application without further notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purposes. Conditions of application and service may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.